

EBC-3220

Compact Embedded Chassis for IEC Single Voltage Mini-ITX SBC

New



Features


- ◆ Design for Mini-ITX SBC with single voltage input
- ◆ Space critical application
- ◆ One 2.5" hard drive capacity
- ◆ Cost-effective, RoHS compliant design

Specifications

Model Name	EBC-3220
SBC Form Factor	Mini-ITX (Single Voltage input)
Cooling Fan	1 x 4 cm
Storage	1 x 2.5" HDD Bracket
Buttons	Power switch
Color	Black
Dimensions (W x D x H)	190mm x 180mm x 55mm
Weight	1KG / 2KG
Operating temperature	-10°C ~ 50°C with air flow*
Mounting	Desktop, wall mount, VESA mount

*Ambient air speed pre IEC-68-2-2 standard

Dimensions (Unit: mm)



Compatible Mini-ITX SBC

Part No.	Expansion Type	Recommend CPU cooler
KINO-DQM871	PCIe x16	CF-989A-RS-R12
KINO-QM770	PCIe x16	CF-989A-RS-R12
KINO-CV/D25501/N26001	PCI	Fanless
KINO-QM670	PCIe x16	CF-989A-RS-R12
KINO-QM57A	PCIe x16	CF-989A-RS-R12
KINO-HM551	PCIe x16	CF-989A-RS-R11
KINO-PV-D5252	PCI or PCIe x1	Fanless
KINO-945GSE2	PCI	Fanless

Packing List

- 1 x QIG
- 1 x Wall mount bracket kit
- 1 x Screw set

Ordering Information

Part No.	Description
EBC-3220-R10	Mini-ITX embedded chassis, for DC input model only, with one 2.5" HDD, w/o power adapter, Black, RoHS
EBC-3220W-R10	Mini-ITX embedded chassis, for DC input model only, with one 2.5" HDD drive bay, 802.11b/g/n 2T2R wireless LAN, w/o power adapter, Black, R10, RoHS
63040-010060-050-RS	Adapter Power, FSP060-DBAE1, 90~264VAC, 60W, 1500mm, 12VDC, Din 4Pin/lock, CCL, RoHS
63000-FSP084DMBA1308-RS	Adapter Power, FSP084-DMBA1, 90~264VAC, 84W, 1800mm, 12VDC, Din 4Pin/lock, CCL, RoHS
32001-010800-100-RS	Dual port USB cable, 200mm, w/o bracket
19FR124010BL-000003-RS	Fan Module, L=200MM, 4cm, 3 pin, CCL, RoHS
EBC-3220-DH610-R10	Embedded chassis with KINO-DH610, support Intel® Core™ i7/i5/i3, Pentium®, Celeron® CPU, one 2.5" HDD drive bay, w/ 19V/6.32A 120W power adapter (support up to 65W CPU), Black, R10, RoHS
EBC-3220W-DH610-R10	Embedded chassis with KINO-DH610, support Intel® Core™ i7/i5/i3, Pentium®, Celeron® CPU, one 2.5" HDD drive bay, 802.11b/g/n 2T2R wireless LAN, w/ 19V/6.32A 120W power adapter (support up to 65W CPU), Black, R10, RoHS
CPU-DT-i5-2500T	Intel® Core™ i5-2500T processor, LGA1155, quad core 2.3GHz, 6M cache, 45W, compatible with CF-1156D-RS CPU cooler
CPU-DT-i5-2390T	Intel® Core™ i5-2390T processor, LGA1155, dual core 2.7GHz, 3M cache, 35W, AMT, compatible with CF-1156D-RS CPU cooler
CPU-DT-i3-2100T	Intel® Core™ i3-2100T processor, LGA1155, dual core 2.5GHz, 3M cache, 35W, compatible with CF-1156D-RS CPU cooler
CPU-DT-P-G620T	Intel® Pentium® G620T processor, LGA1155, dual core 2.2GHz, 3M cache, 35W, compatible with CF-1156D-RS CPU cooler
CPU-DT-C-G440	Intel® Celeron® G440 processor, LGA1155, single core 1.6GHz, 1M cache, 35W, compatible with CF-1156D-RS CPU cooler
CF-1156D-RS	LGA1155/LGA1156 cooler kit, 1U chassis compatible 65W