
# PAC-400G

#### 5-slot Half-size Compact Chassis



#### **Features**

- ◆ RoHS compliant design
- ◆ Two USB ports on the front panel
- ♦ One, 8 cm hot swappable fan
- ♦ One 3.5" internal HDD bay
- ◆ One 3.5" drive bay, for optional removable drive
- ◆ Supports Pentium 4 half-size CPU card


#### **Specifications**

◆ Construction	Heavy duty metal			
♦ SBC Form Factor	Half-size, slot SBC			
♦ Drive Bays	1 x 3.5" HDD			
♦ Cooling Fans	1 x 8 cm			
♦ I/O Ports	2 x USB			
♦ I/O Openings	1 x LPT, 1 x COM			
♦ Expansion Slots	5 slots			
♦ Indicators	Power, HDD			
♦ Buttons	Power switch, reset			
♦ Operating Temperature	0°C ~ 50°C			
♦ Operation Humidity	10% ~ 90%			
♦ Color	W: White			
♦ Weight (Net/Gross)	3.8 kg/5.6 kg			
♦ Dimensions (DxWxH)	269 mm x 140 mm x 230.5mm			

## **Ordering Information**

Part No.	Description			
PAC-400GW-R11/916AP	5-slot half-size chassis, white, with ACE-916AP-RS, RoHS			
PAC-400GW-R11/A618A	5-slot half-size compact chassis, white, 1 x 8 cm fan, with ACE-A618A-RS-R11 (180W ATX model), RoHS $$			
7G000-ST1110L-RS	3.5" SATA removable drive bay with keylock, white, $\ensuremath{RoHS}$			

#### Dimensions (measurement units: millimeter)



# **Backplane Options**

Model No. SBC Type	PCI	ISA	PCle			PSU Connector	
	овс туре	PCI	ISA	x1	х4	x16	PSU Connector
BP-4S-RS	ISA	0	4	0	0	0	AT
IP-4S-RS	PCISA	3	0	0	0	0	AT
IP-4S2-RS	PCISA	2	1	0	0	0	AT
IP-4S3-RS	PCISA	0	3	0	0	0	AT
IP-4S4-RS	PCISA	0	3	0	0	0	AT
IP-4SA-RS	PCISA	3	0	0	0	0	ATX
IP-4S2A-RS	PCISA	3	0	0	0	0	ATX
HPE-4S1	PCI/PICOe	3	0	0	0	0	ATX
HPE-4S2	PCI/PICOe	2	0	0	1	0	ATX

## **Power Supply Options**

Туре	Model No.	Watt
AT	ACE-916AP-RS	150W
ATX	ACE-A618A-RS-R11	180W

PAC-400G supports single 1U height PSU. For more IEI PSU models, please refer to section 5 or visit www.ieiworld.com.