RACK-500G

5U 5-slot Full-size Rackmount Chassis




Features

- ◆ RoHS compliant design
- ♦ 2 x USB ports on front panel
- ♦ 1 x front-accessible 3.5" and 1 x 3.5" HDD drive capacity
- ◆ Hot-swappable 8 cm cooling fan
- ◆ 19" rack-mountable carrier (optional)

Specifications

◆ Construction	Heavy duty metal			
♦ SBC Form Factor	Full-size, slot CPU cards			
♦ Drive Bays	1 x front-accessible 3.5"			
	1 x 3.5" HDD			
♦ Cooling Fans	1 x 8 cm			
♦ I/O Ports	2 x USB			
♦ I/O Openings	1 x LPT, 1 x COM			
♦ Expansion Slots	5 slots			
♦ Indicators	Power, HDD			
♦ Buttons	Power switch, reset			
♦ Operating Temperature	0°C ~ 50°C			
♦ Operation Humidity	10% ~ 90%			
♦ Color	W: White/B: Black			
♦ Weight (Net/Gross)	6 kg/9 kg			
♦ Dimensions (DxWxH)	440.2 mm x 110.6 mm x 221.3 mm			

Dimensions (measurement units: millimeter)



Backplane Options

Model No. SBC	CDC Tuna	PCI	ISA	PCle			PSU
Wodel No.	SBC Type	PCI ISA		x1	х4	x16	Connector
PCI-5S2-RS	PICMG 1.0	4	1	0	0	0	AT
PCI-5S2A-RS	PICMG 1.0	4	1	0	0	0	ATX
PE-5S2	PICMG 1.3	0	0	3	0	1	ATX
PE-5S	PICMG 1.3	2	0	0	1	1	ATX
HPE-5S1	PCI/PICOe	4	0	0	0	0	ATX
HPE-5S2	PCI/PICOe	4	0	0	0	0	ATX
HPE-5S3	PCI/PICOe	2	0	2	0	0	ATX

Only R20 or later versions support PICMG 1.3 backplane.

Ordering Information

Part No.	Description
RACK-500G C -R21/A618A	5U 5-slot full-size chassis, (Black/White), 1 x 8 cm fan, with ACE-A618A-RS-R11 (180W ATX model), RoHS PSU
CA-950G C	19" rack carrier for RACK-500G and RACK-900G, (Black/White), RoHS

C Color Code: B-Black W-White

Power Supply Options

Туре	Model No.	Watt
AT	ACE-916AP-RS	150W
ATX	ACE-A618A-RS-R11	180W
	ACE-A225A-RS	250W

RACK-500G supports single 1U height AT type PSU. For more IEI PSU models, please refer to section 5 or visit www.ieiworld.com.